

Restraint Capture Tunnel

Catalog # 46280

Made with Aluminum and Stainless Steel materials. Approximate Dimensions of Tunnel are 18" wide x 28" tall x 75" long. Tunnel is 22" tall from casters, 28" overall with casters. Tunnel has Handles both ends for maneuvering. Supported on four 5" SS Casters. Tunnels made to pair with one another in several configurations. Tunnels will be divided into 3 equal sized chambers. Section closest to cage end will have restraint system. Restraint Wall to have a "Speedy" SS Acme Screw to expedite restraint wall. Restraint Wall operated by Wheel and will ride on support guides. Fixed Wall behind Restraint Wall provided to match rest of Tunnel. (2) Chambers have flip up Top Door Panels made out of 1" x 1" SS Wire Panel. Guillotine Doors on each end and center areas with secure SS Latches provided. Guillotine Doors & Latches will be able to lock in the open and closed positions. (5) Identical Guillotine Doors per Tunnel, ~17.5" wide x 25.5" tall. A Guillotine Door provided at center of one side of Tunnel to pair in "T" config. Removable Waste Pans under each chamber. Floor of Tunnel is 1" wide flat bar with $\frac{1}{2}$ " gaps running the width of Tunnel. "D" Rings attached to each side of the Tunnels for ratchet strap connection. Needs to pair with cage end and Tunnel ends.

Tunnel walls are 3/8" Dia. Horizontal rods on 7/8" centers. Bead Blasted to a Matte Finish.





